

INSTALLATION INSTRUCTION FOR 6891

For Wall Mount Light Fixtures

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

READ AND SAVE THESE INSTRUCTIONS

PREPARATION

1. Shut off the power at the fuse box or circuit breaker box. If necessary, remove the old fixture and all mounting hardware from wall junction box.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to loose any small parts necessary for installation.

MOUNTING THE FIXTURE (FIG.1)

3. The circular strap (B) contains several pairs of threaded holes, Find the pair of holes that match the hole spacing in your fixture face plate (D) and thread the two mounting screws (A) part way into the circular strap (B). Secure circular strap (B) to outlet box (not provided) with outlet box screws (C) through slotted holes in circular strap. The side marked "GRD" must face outward.

CONNECTING THE WIRES (Fig. 2)

4. Connect the fixture wires to the junction box wires as shown in Fig. 2. Make sure all wire connectors are secure and do not easily pull off with a slight tug. If there is no green ground wire from the junction box, connect the fixture ground wire to the circular strap or the crossbar with the green screw provided.
5. Tuck these wire connections neatly into the wall junction box.
6. Raise the face plate (D) allowing for the mounting screws (A) to protrude through the holes on face plate (D), and secure with the ball nut (E).

COMPLETING THE INSTALLATION

7. Install the proper light bulbs for your fixture.
DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).
8. Place the glass (G) onto the arm (F) of the face plate (D).

Return the power to the junction box and test the fixture. Your installation is now complete.

MIN 90°C SUPPLY CONDUCTOR

