

# INSTALLATION INSTRUCTION

Item#772 (New. 12/01/2011)

READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**  
**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR**

## ASSEMBLING THE FIXTURE (Fig. 1)

1. Shut off the power at the circuit breaker (**avertissement! couper le courant au niveau des fusibles ou du disjoncteur**) and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Thread mounting screw (A) into the pre-drilled holes in the circular strap (B) spaced the same distance apart as the holes in the back-plate and secure with hex nut (C).
4. Attach the circular strap (B) to the junction box with junction box screws (D). The side of the circular strap marked "GND" must face out.

## CONNECTING THE WIRES (Fig. 2)

5. At this point, connect the electrical wire as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture ground wire directly to the circular strap using the green screw provided. After wires are connected, tuck them carefully inside the junction box.

## COMPLETING THE INSTALLATION (Fig. 1)

6. Place the fixture body (K) over the mounting screws (A) and secure tightly with cap nuts (E).
7. Place the candle sleeve (G) onto the socket (F).
8. Install the light bulb(s) (I) (not included) in accordance with the fixture's specifications. (**DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**) (**NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!**)
9. Clip the fabric shade(s) (H) onto the bulb(s). Hang the crystal drops (J) to the front edge of the metal leave on each arm.

Your installation is now complete. Return the power to the junction box and test the fixture.

**Note:** Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

